



EFG014025

## EFG IZI Pro

EFG Izi Pro is a table range with adjustable T-foot and rectangular legs. The placement of the thickest part of the leg is upwards. The table has metal frame and is equipped with motor-driven height adjustment. EFG Izi Pro F has table tops with bevelled edges and EFG Izi Pro S has straight edges.

## Product info

- With EFG Izi Pro workstations you have the possibility to combine table tops and frames within the limits that design and standard allows.
- EFG Izi Pro has a large number of table tops.
- F model: Table tops with a core of 22 mm MDF, veneered with 0,6 mm in beech and birch with bevelled edges.
- S model: Table tops with a core of 22 mm chipboard, veneered with 0,6 mm in beech and birch with straight edges. Table tops in laminate (MB, MR, ME, MV, M6 and M8) have a core of 22 mm chipboard and straight edges.
- Table tops with straight edges (S-model) available in high pressure laminate, white (HV), in selected sizes.
- The frame is available with both two or three legs.
- Motor-driven height adjustment with two motors, two strokes: 500 or 650 mm. 680-1180 mm or 640-1290 mm.
- Available with sliding table top as additional for an easy cable access and to create a clean surface. Please note that the smallest table top size is 1400 mm when choosing sliding table top.
- Metal frame with rectangular legs with the placement of the thickest part upwards and T-foot. Black structure (24), dark grey metallic (26), or white (Z4).
- The frame has adjustable beams between the lengths 1000 and 1800 mm, which is suitable for table tops from 1200 to 2000 mm.
- Maximum loading: 100 kg, spread over the table top.
- Assembling: Frame is fixed directly to the table top with enclosed screws.
- Accessories: Desk screens, modesty panels, cable management, CPU-holder and wall mount for flat screens.
- Guarantee: Five years liability for defects resulting from faulty design, materials or workmanship.
- Complies with established criteria for furniture eco-labelling. Minor deviations may occur.
- Tested according to: EN 527-1, EN 527-2, EN 527-3. The tables are CE marked and fulfill AFS 2008:3 and AFS 2009:5, (European directive 2006/42/EG.) ISO 21016:2007: 6.1, 6.5, 6.6

### TECHNICAL INFO:

- Power supply: 240 V.
- Speed, 45 kg: 32 mm/s.
- Stroke 500 och 650 mm.
- Maximum load: 100 kg (incl table top 25 kg)
- Overheating protection: 1 min operation, 9 min rest.
- Sound 45 dB
- Consumption in standby: 0,10 W (two legs) 0,20 W (Three legs)
- Temperature in the surroundings during operation: +5 till +40° C

EFG014028



EFG Izi Pro, two legs, LO

EFG014036



EFG Izi Pro, two legs, HI

EFG014030



EFG Izi Pro, three legs, LO

EFG014031



EFG Izi Pro, three legs, HI

EFG014033



EFG Izi pro, height adjustment